

VAN PHUOC TAPE JOINT STOCK COMPANY
ADD: 1/3 TO KY, AP DONG, THOI TAM THON, HOC MON, HO CHI MINH CITY,
VIETNAM

TEL: 84-903-817 113 FAX: 848-371-333097 [Email: bangkeovanphuocvn@gmail.com](mailto:bangkeovanphuocvn@gmail.com)

-----000-----

CERTIFICATE OF ANALYSIS

We hereby certify that the delivered product fulfill the following specifications:

Material: Polyetylen

Mode: Sabic 218B (parameters the attached)

Colour: Clear

Specific Gravity: 0.92g/cm³

Exxon Mobil Metallocene: 3%

Capacity: 260met/ roll

Net pe: 2.1kg

Total weight: 2kg3

No	Specifition		Tolerance	Actual	Reference
01	Width (mm)	500 ± 3	Max:515 Min: 505	510	
02	Thickness(mm)	0.017 ± 2%	Max:0.0175 Min: 0.0162	0.0169	
03	Length m/kg	130 ± 2%	Max:132 Min: 129	130.5	
04	Stretch	200% ± 5%	Max:205 Min: 190	197.5	
05	Tensile N/mm ²	25			
06	Additive	No slip, no anti - block			

VAN PHUOC TAPE JSC.

DATA SHEET SPECIFICATIONS

DESCRIPTION

OPP Packaging Tape is a high tack adhesive tape of biaxially oriented polypropylene film coated with emulsion based acrylic adhesive . It has excellent adhesion and shear resistance to variety carton surfaces.

APPLICATION

- > Medium to heavy carton sealing applications
- > Bundling and strapping
- > Sealing cartons and holding applications with materials that stored in extreme temperature
- > For outdoor storage

PHYSICAL PROPERTIES

	METRIC
Product Code	OPP
Backing	BOPP Film
Adhesive Type	Acrylic Emulsion
Total Thickness	0.050 mm
Film Thickness	0.028 mm
Adhesive Thickness	0.022 mm
Adhesion to Steel	> 6.3 N/25 mm
Adhesion to Fiber	> 6.3 N/25 mm
Holding Power	Hour < 48

TEST METHOD

PSTC Method

AVAILABLE COLOR (S)

Clear
Yellow
Tan

STANDARD WIDTH(S)

2" (48 mm) 2.5" (60 mm) 3" (72 mm)

STANDARD LENGTH (S)

45 y (40.5 m) 50 y (45 m) 100 y (90 m)
1000 y (900 m)

** others sizes and lengths are available upon request **

STORAGE & USAGE CONDITIONS

Tape should be stored in its original in a cool,dry area away from direct sunlight and should be used within 12 months of date

